

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product code : VP3001DD01
 Product name : Novaset® 4401/40 ECO NEUTRAL;neutral coa
 SDS # : 4r4g:g42o:8j8

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Product for the graphic arts industry
 Uses advised against : None known.

1.3 Details of the supplier of the safety data sheet

Manufacturer / Distributor : Flint CPS Inks Germany GmbH
 Sieglestrasse 25
 D-70469 Stuttgart
 GERMANY
 e-mail address of person responsible for this SDS : MSDS.Germany.Stuttgart.SF@flintgrp.com

1.4 Emergency telephone number (with hours of operation)

Supplier

+49 (0) 621-60-43333 24 h

National Poisons Information Service (NPIS) : 0844 892 0111 Hours of operation 24/7 - Medical professionals (NHS) only

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Eye Dam. 1, H318

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H318 - Causes serious eye damage.

Precautionary statements : P280 - Wear protective gloves and eye or face protection.
 P305 + P351 - IF IN EYES: Rinse cautiously with water for several minutes.
 P338 - Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 - Immediately call a POISON CENTER or physician.

Supplemental label elements : Not applicable.

Hazardous ingredients : docusate sodium

Annex XVII - Restrictions : Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Novaset® 4401/40 ECO NEUTRAL;neutral coa

SECTION 2: Hazards identification

2.3 Other hazards

PBT : P: Not available. B: Not available. T: Not available.

vPvB : vP: Not available. vB: Not available.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Type
			Regulation (EC) No. 1272/2008 [CLP]	
docusate sodium	REACH #: 01-2119491296-29 EC: 209-406-4 CAS: 577-11-7	≤5	Skin Irrit. 2, H315 Eye Dam. 1, H318	[1]
Alcohols, C16-C18, ethoxylated	EC: 500-212-8 CAS: 68439-49-6	≤0.3	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 3, H412	[1]

See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

[6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Eye contact** : Remove contact lenses, if present and easy to do. Rinse cautiously with water for several minutes. Seek immediate medical attention/advice.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Give nothing by mouth. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Novaset® 4401/40 ECO NEUTRAL;neutral coa

SECTION 4: First aid measures

Use suitable protective equipment (section 8).

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

See toxicological information (Section 11)

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable Extinguishing media : Recommended:, alcohol-resistant foam, CO₂, powders, water spray

Extinguishing media not to be used : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

Decomposition products may include the following materials:

carbon dioxide
carbon monoxide
nitrogen oxides
sulfur oxides
metal oxide/oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Do not release runoff from fire to drains or watercourses.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

6.3 Methods and materials for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

6.4 Reference to other sections

- See Section 1 for emergency contact information.
See Section 13 for additional waste treatment information.
See Section 8 for information on appropriate personal protective equipment.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep container tightly closed. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Remove contaminated clothing and protective equipment before entering eating areas. Workers should wash hands and face before eating, drinking and smoking. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8). Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with all local, regional, national and international regulations.
Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10).
Observe label precautions. Keep container tightly closed and in a well-ventilated place.
Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.
Storage temperature: 5 to 35°C

7.3 Specific end use(s)

Not applicable.

Additional information

Not applicable.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

- Occupational exposure limits** : Not applicable.
- Other Exposure limits** : CMR: See toxicological information (Section 11)
- Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace

SECTION 8: Exposure controls/personal protection

atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

No DNELs/DMELs available.

PNECs

No PNECs available.

8.2 Exposure controls

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction.

Individual protection measures

Respiratory protection

: Not applicable.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Hand protection / Gloves

: Avoid all skin contact with product, clean up contamination/spills as soon as they occur.
Wear gloves (tested to EN374) if hand contamination likely, wash off any skin contamination immediately.
Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop.
For prolonged or repeated handling, use the following type of gloves:

Recommended: polyethylene (PE), Viton®/butyl rubber

Recommended (breakthrough time): > 8 hours

May be used (breakthrough time): 1 - 4 hours

Not recommended (breakthrough time): < 1 hour

Recommended thickness: ≥ 0.2 mm

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

References: <http://www.esig.org/en/library/publications/best-practice-guides>

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Eye/face protection

: Use eye protection according to EN 166.
Use safety eyewear designed to protect against splash of liquids.

Environmental exposure controls

Do not allow to enter drains or watercourses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	Liquid.
Color	White.
Odor	Slight

Novaset® 4401/40 ECO NEUTRAL;neutral coa

SECTION 9: Physical and chemical properties

Odor threshold	-	Not determined.
pH	8 - 9.5	
Melting point	-	Not relevant/applicable due to nature of the product.
Boiling point	>= 100 °C (water)	
Flash point	Closed cup: > 100°C	theoretical
Evaporation rate (butyl acetate = 1)	-	Not determined.
Flammability (solid, gas)		Not applicable. Liquid.
Burning rate	-	Not determined.
Burning time	-	Not determined.
Explosion limits		
Lower:	-	Not determined.
Upper:	-	Not determined.
Vapor pressure	< 23 hPa (water)	
Vapor density	-	Not determined.
Density	~ 1 g/cm ³ (20 - 25 °C)	
Solubility	Partially soluble in the following materials: Water	
Partition coefficient: n-octanol/ water	-	Not determined.
Auto-ignition temperature	-	Not determined.
Decomposition temperature	-	Not determined.
Viscosity		Not determined.
Explosive properties	-	Not determined.
Oxidizing properties	-	Not determined.

9.2 Other information

SADT : Not available.

SECTION 10: Stability and reactivity

10.1 Reactivity

Not available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (see Section 7).

10.3 Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

Date of issue/Date of revision : 11.10.2019
Version : 2

Novaset® 4401/40 ECO NEUTRAL;neutral coa

SECTION 10: Stability and reactivity

10.5 Incompatible materials

Keep away from the following materials to prevent strong exothermic reactions:
oxidizing agents, strong alkalis, strong acids

10.6 Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

There are no data available on the mixture itself. The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended. See sections 2 and 3 for details.

Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage.

Substances / Mixtures

Acute toxicity :

Product/ingredient name	Result	Species	Dose	Exposure
docusate sodium	LD50 Dermal	Rabbit	>10 g/kg	-
Alcohols, C16-C18, ethoxylated	LD50 Oral	Rat	1260 mg/kg	-

Acute toxicity estimates

Not available.

Irritation/Corrosion : Causes serious eye damage.

Sensitization : Not available.

Mutagenicity : Not available.

Carcinogenicity : Not available.

Reproductive toxicity : Not available.

Specific target organ toxicity (single exposure) : Not available.

Specific target organ toxicity (repeated exposure) : Not available.

Aspiration hazard : Not available.

Chronic toxicity : Not available.

Teratogenicity : Not available.

Other information

Toxicokinetics

Absorption : Not available.

Distribution :

Metabolism : Not available.

Elimination : Not available.

SECTION 12: Ecological information

There are no data available on the mixture itself. Do not empty into drains or watercourses. See Sections 2 and 3 for details.

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
docusate sodium	Acute EC50 39.5 mg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours

12.2 Persistence and degradability

Date of issue/Date of revision : 11.10.2019
Version : 2

Novaset® 4401/40 ECO NEUTRAL;neutral coa

SECTION 12: Ecological information

Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
docusate sodium	-	9.33	low

12.4 Mobility in soil

Not available.

12.5 Results of PBT and vPvB assessment

PBT : P: Not available. B: Not available. T: Not available.

vPvB : vP: Not available. vB: Not available.

12.6 Other adverse effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Hazardous waste : Yes.

European waste catalogue (EWC)

Waste code	Waste designation
08 03 12*	waste ink containing dangerous substances

SECTION 14: Transport information

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

International transport regulations

14.1 UN number : Not regulated.

14.2 Proper shipping name : -

14.3 Transport hazard class(es) : -

14.4 Packing group : -

14.5 Environmental hazards : Not applicable.

14.6 Special precautions for user : Not applicable.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

Date of issue/Date of revision : 11.10.2019
Version : 2

Novaset® 4401/40 ECO NEUTRAL;neutral coa

SECTION 15: Regulatory information

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

VOC content : < 0,1 %

Europe inventory : All components are listed or exempted.

National regulations

Industrial use : The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

15.2 Chemical Safety Assessment

Mixture No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 DMEL = Derived Minimal Effect Level
 DNEL = Derived No Effect Level
 EUH statement = CLP-specific Hazard statement
 PBT = Persistent, Bioaccumulative and Toxic
 PNEC = Predicted No Effect Concentration
 RRN = REACH Registration Number
 vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Eye Dam. 1, H318	Calculation method
Full text of abbreviated H statements :	H315 Causes skin irritation. H318 Causes serious eye damage. H400 Very toxic to aquatic life. H412 Harmful to aquatic life with long lasting effects.
Full text of classifications [CLP/GHS] :	Aquatic Acute 1, H400 AQUATIC HAZARD (ACUTE) - Category 1 Aquatic Chronic 3, H412 AQUATIC HAZARD (LONG-TERM) - Category 3 Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2

Date of printing : 11.10.2019

Date of issue/ Date of revision : 11.10.2019

Date of previous issue : 22.12.2018

Version : 2

Notice to reader

Novaset® 4401/40 ECO NEUTRAL;neutral coa

SECTION 16: Other information

The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.